



AUSTRAL PLYWOODS



Impact Structural Plywood

Protect yourself.

- ✓ Suitable for Cyclone Shelters / Region "D"
- ✓ AS/NZS 1170.2 Tested ("Flying Debris")
- ✓ F14/F17 Stress Grade
- ✓ Complies with Australian Standards



SPECIFICATION SHEET

IMPACT STRUCTURAL PLYWOOD



AUSTRAL PLYWOODS

Manufactured by Rimbunan Hijau (PNG) Group
Distributed by Austral Plywoods Pty Ltd

An F14/F17 panel built to strict structural standards.

IMPACT STRUCTURAL is structural plywood manufactured to AS/NZS 2269. Utilising a phenolic “A” bond, it is recognised as an engineered panel under AS1720. It is suitable for most structural applications where visual appearance is unimportant.

IMPACT STRUCTURAL is manufactured in accordance with the independent quality control program audited by the Engineered Wood Panels Association of Australasia and bears the PAA JAS-ANZ label, your guarantee of compliance.



Standard:-	AS/NZS 2269 Structural Plywood
Sheet Sizes	
Length:-	2400mm
Width:-	1200mm
Thickness:-	7, 9, 12, 15, 17, 19, 21, 25mm
Veneer Grade:-	C grade Face / D grade Back
Stress Grade:-	F14/F17
Impact penetration:-	AS/NZS 1170.2 tested (“flying debris”)
Density:-	Approx 700kg/m ³
Timber Species:-	Mixed Hardwoods
Tolerances:-	As per AS/NZS 2269
Moisture Content:-	8 – 15% (Despatch)
Adhesive:-	Phenolic – AS2754.1
Bond:-	Type A – AS/NZS 2098.2
Finish:-	Smooth sanded one side
Edge Profile:-	Square edge

For more information and a **FREE SAMPLE** contact us on 07 3426 8666

www.AUSTRALPLY.com.au