

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST

Chemwatch Independent Material Safety Data Sheet

Issue Date: 2-Aug-2011

A317LP

CHEMWATCH 4729-83

Version No:9

CD 2012/2 Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST

PRODUCT USE

Used in residential, commercial and industrial construction, furniture and fitments and/or general purpose building.

SUPPLIER

Company: Carter Holt Harvey (CHH) Wood Products

Address:

PO Box 425

Box Hill

VIC, 3128

Australia

Telephone: +61 3 9258 7600

Fax: +61 3 9258 7629

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

RISK

•None under normal operating conditions.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
wood veneer		>90
impregnation residuals, as		<10
tebuconazole	107534-96-3	^
propiconazole	60207-90-1	^
permethrin	52645-53-1	^
3- iodo- 2- propynyl butyl carbamate	55406-53-6	^
2- ethylhexanoic acid, zinc salt	136-53-8	^
white spirit	8052-41-3.	^
In use, may generate wood dust softwood	Not avail.	

THIS REPORT IS FOR TREATED PRODUCT ONLY

Section 4 - FIRST AID MEASURES

SWALLOWED

- Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations.
- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

continued...

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST

Chemwatch Independent Material Safety Data Sheet

Issue Date: 2-Aug-2011

A317LP

CHEMWATCH 4729-83

Version No:9

CD 2012/2 Page 2 of 8

Section 4 - FIRST AID MEASURES

EYE

• Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations.

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

■ Brush off dust.

In the event of abrasion or irritation of the skin seek medical attention.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

■ Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

■ Alert Fire Brigade and tell them location and nature of hazard.

Use water delivered as a fine spray to control the fire and cool adjacent area.

FIRE/EXPLOSION HAZARD

- Combustible. Will burn if ignited.
- Wood products do not normally constitute an explosion hazard.
- Mechanical or abrasive activities which produce wood dust, as a by-product, may present a severe explosion hazard if a dust cloud contacts an ignition source.
- Hot humid conditions may result in spontaneous combustion of accumulated wood dust.
- Partially burned or scorched wood dust can explode if dispersed in air.
- Wet dusts may ignite spontaneously.
- Solid fuels, such as wood, when subjected to a sufficient heat flux, will degrade, gasify and release vapours. There is little or no oxidation involved in this gasification process and thus it is endothermic. This process is referred to as forced pyrolysis but is sometimes referred to, wrongly, as smoldering combustion. This type of combustion, once initiated, can continue in a low-oxygen environment, even when the fire is in a closed compartment with low oxygen content.
- An airborne concentration of 40 grams of dust per cubic meter of air is frequently used as the lower explosive limit (L.E.L) of wood dusts.
- Thermal oxidative decomposition may produce vapours and gases including carbon monoxide, aldehydes (including formaldehyde), organic acids, cyanides, polycyclic aromatics, and other volatile organic fragments.

FIRE INCOMPATIBILITY

Avoid exposure to excessive heat and fire.

HAZCHEM

None

continued...

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST

Chemwatch Independent Material Safety Data Sheet

Issue Date: 2-Aug-2011

A317LP

CHEMWATCH 4729-83

Version No:9

CD 2012/2 Page 3 of 8

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

Pick up.

Refer to major spills.

MAJOR SPILLS

Pick up.

Secure load if safe to do so.

Bundle/collect recoverable product.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Use gloves when handling product to avoid splinters.

SUITABLE CONTAINER

- Generally not applicable.

STORAGE INCOMPATIBILITY

- Keep dry.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry area protected from environmental extremes.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.

For major quantities:

- Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams).
- Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA mg/m ³	STEL mg/m ³	Notes
Australia Exposure Standards	white spirit (White spirits)	790		(see Chapter 16)
Australia Exposure Standards	wood dust softwood (Wood dust (soft wood))	5	10	Sen

The following materials had no OELs on our records

- tebuconazole: CAS:107534- 96- 3
- propiconazole: CAS:60207- 90- 1 CAS:75881- 82- 2

continued...

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST

Chemwatch Independent Material Safety Data Sheet

Issue Date: 2-Aug-2011

A317LP

CHEMWATCH 4729-83

Version No:9

CD 2012/2 Page 4 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- permethrin: CAS:52645- 53- 1 CAS:54774- 45- 7 CAS:57608- 04- 5 CAS:93388- 66- 0
CAS:63364- 00- 1 CAS:60018- 94- 2 CAS:75497- 64- 2
- 3- iodo- 2- propynyl butyl carbamate: CAS:55406- 53- 6
- 2- ethylhexanoic acid, zinc salt: CAS:136- 53- 8 CAS:157321- 97- 6

MATERIAL DATA

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST:

None assigned.

WOOD DUST SOFTWOOD:

■ Wood dusts produce dermatitis and an increased risk of upper respiratory disease. Epidemiological studies in furniture workers show an increased risk of lung, tongue, pharynx and nasal cancer. An excess risk of leukaemia amongst millwrights probably is associated with exposure to various components used in wood preservation.

Impairment of nasal mucociliary function may occur below 5 mg/m³ and may be important in the development of nasal adenocarcinoma amongst furniture workers exposed to hardwoods.

Certain exotic hardwoods contain alkaloids which may produce headache, anorexia, nausea, bradycardia and dyspnoea.

The softwood TLV-TWA reflects the apparent low risk for upper respiratory tract involvement amongst workers in the building industry. A separate TLV-TWA, for hard woods, is based on impaired nasal mucociliary function reported to contribute to nasal adenocarcinoma and related hyperplasia found in furniture workers.

PERSONAL PROTECTION

EYE

- When sawing, machining or sanding use
- Safety glasses with side shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Protective gloves eg. Leather gloves or gloves with Leather facing.
- Safety footwear.

OTHER

- No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

RESPIRATOR

- Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

continued...

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST

Chemwatch Independent Material Safety Data Sheet

Issue Date: 2-Aug-2011

A317LP

CHEMWATCH 4729-83

Version No:9

CD 2012/2 Page 5 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

• Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations. Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Plywood in all sizes, impregnated with liquid treatment; can give off white spirit odour. THIS CHEMWATCH REPORT IS FOR TREATED PRODUCT ONLY.

PHYSICAL PROPERTIES

Does not mix with water.

State	Manufactured	Molecular Weight	Not Applicable
Melting Range (°C)	Not Applicable	Viscosity	Not Applicable
Boiling Range (°C)	Not Applicable	Solubility in water (g/L)	Immiscible
Flash Point (°C)	Not Applicable	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Applicable
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	Not Available
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Applicable
Volatile Component (%vol)	Not Applicable	Evaporation Rate	Not Applicable

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

■ Product is considered stable and hazardous polymerisation will not occur.
For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Not normally a hazard due to physical form of product.
Considered an unlikely route of entry in commercial/industrial environments.

continued...

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST

Chemwatch Independent Material Safety Data Sheet

Issue Date: 2-Aug-2011

A317LP

CHEMWATCH 4729-83

Version No:9

CD 2012/2 Page 6 of 8

Section 11 - TOXICOLOGICAL INFORMATION

Ingestion of sawdust may cause nausea, abdominal pain, vomiting or diarrhoea.

EYE

■ The dust may produce eye discomfort causing smarting, pain and redness.

SKIN

The dust is discomforting and mildly abrasive to the skin and may cause drying of the skin, which may lead to contact dermatitis.

INHALED

■ Not normally a hazard due to physical form of product.

Generated dust may be discomforting.

CHRONIC HEALTH EFFECTS

• Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations.

Various woods are able to induce allergies, both of the immediate onset type in woodwork which causes a respiratory syndrome, and of the delayed type which results in eczema from exposure to dusts and direct contact. Cross-reaction is common. Certain alkaloids are contained in some species, causing headache, anorexia, slow heart rate and breathing difficulties. Conjunctivitis is also possible. Allergic reactions are aggravated by fungi and bacteria associated with wood. Cancers of the respiratory tract seem to be more common in those professions associated with the use of wood. This seems to be true for both hardwood and soft wood.

Wood dust may cause skin and respiratory sensitisation.

TOXICITY AND IRRITATION

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST:

■ Not available. Refer to individual constituents.

WOOD DUST SOFTWOOD:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

■ Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Allergy causing activity is due to interactions with proteins.

Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema.

Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.

No significant acute toxicological data identified in literature search.

WARNING: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS.

WARNING: Inhalation of wood dust by workers in the furniture and cabinet making industry has been related to nasal cancer [I.L.O. Encyclopedia] Use control measures to limit all exposures.

continued...

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST

Chemwatch Independent Material Safety Data Sheet

Issue Date: 2-Aug-2011

A317LP

CHEMWATCH 4729-83

Version No:9

CD 2012/2 Page 7 of 8

Section 12 - ECOLOGICAL INFORMATION

WOOD DUST SOFTWOOD:

- DO NOT discharge into sewer or waterways.

Although treated, the solid wood will decay on ground contact.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
wood dust softwood	No Data Available	No Data Available		

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE None

REGULATIONS

Regulations for ingredients

No data for CHH LOSP Azole Treated Pine Plywood, LVL and I Joist (CW: 4729-83)

No data for wood dust softwood (CAS: , Not avail)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
propiconazole	60207- 90- 1, 75881- 82- 2
permethrin	52645- 53- 1, 54774- 45- 7, 57608- 04- 5, 93388- 66- 0, 63364- 00- 1, 60018- 94- 2, 75497- 64- 2
2- ethylhexanoic acid, zinc salt	136- 53- 8, 157321- 97- 6

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

continued...

CHH LOSP AZOLE TREATED PINE PLYWOOD, LVL AND I JOIST

Chemwatch Independent Material Safety Data Sheet

Issue Date: 2-Aug-2011

A317LP

CHEMWATCH 4729-83

Version No:9

CD 2012/2 Page 8 of 8

Section 16 - OTHER INFORMATION

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 2-Aug-2011

Print Date: 25-Jun-2012

This is the end of the MSDS.