

The **Enviroven** collection of timber veneers features a stunning selection of colours and textures, in traditional woodgrains and fresh, innovative designs. All our veneers are reconstructed for consistent and repeatable colour, tone and grain structure across each panel; creating the ideal choice for large or small installations.

Application

Enviroven Veneers are suitable for any interior application where conventional timber veneers could be used. **Enviroven** is a versatile material ideally suited for, kitchens, bathrooms, commercial fit outs, hospitality and furniture.

Grain direction

The **Enviroven** grain runs vertically along the length of the leaf.

Environmental sensitivity

The timber veneers used in this product are either sourced from sustainably managed forests or poplar plantations, conforming to world's best practice for forest management.

Maintenance

Enviroven surfaces are easy to clean using a cloth dampened with warm water and detergent, or a solution of 1 part methylated spirits to 20 parts water. In case of more resistant stains we recommend to using 100% methylated spirits or other light solvents. If in doubt about a particular cleaner or detergent, check with its manufacturer for the suitability.

Avoid the use of acetone or trichloroethylene for cleaning purposes. Use of abrasive cleaners, powders, scouring pads, steel wool, sandpaper etc. can damage the finish and make the surface susceptible to staining. Accidental spills or splatters from these harsh materials should be wiped off immediately, and the area cleaned thoroughly with a damp cloth. Examples of these materials are: Ceramic cooktop cleaners, tub and tile cleaners, chlorine bleach, oven cleaners, and harsh detergents.

For information regarding touch up and repairs please visit our website newageveneers.com.au

Veneer Source

Enviroven 1 - These Reconstructed veneers are certified by the S.G.S. and are made from plantation poplar which is grown mainly in the Pandania Plain in Northern Italy.

Enviroven 2 - These Reconstructed veneers are made from Obeche (Ayous) veneers which are sourced in Cameroon. These veneers are strictly forest managed using selective harvesting methods. See environmental impact statement for further details.

Enviroven 3 - These reconstructed veneers are made from the Linden Tree grown in European forests.

Technical Advantages

As a reconstructed veneer, **Enviroven** offers consistency in woodgrain structure and tone across each panel, creating the ideal surface for large or small installations.

Due to the manufacturing process predictability is assured over conventional veneers. Consistency is obtained to an acceptable level in colour with only subtle grain difference within block lots of up to 1100 leaves of veneer. In some veneers due to batch dyeing there can be colour variance of up to 10% from block to block. To minimise this occurrence it is important that the specifier advise **New Age Veneers Pty Ltd** in writing of their requirements for large projects.

Enviroven Veneers are supplied unfinished; allowing you to specify the final look of your interior space. The range may also be laid on your substrate of choice and offers a matching selection of machine veneered edging to complete the project.

Technical specifications

Veneer leaf size

2500mm x 640mm x 0.6mm
2800mm x 640mm x 0.6mm
3100mm x 650mm x 0.6mm
2500mm x 1250mm x 0.6mm

Panel Size

2400mm x 1200mm x (variable thickness available - refer to your local veneer layer)
2700mm x 1200mm x (variable thickness available - refer to your local veneer layer)
3000mm x 1200mm x (variable thickness available - refer to your local veneer layer)

Please note: Not every veneer colour is available in all of the sizes listed above. To see which veneers are available in each size group please visit our **Enviroven Veneers** page on our website and click on the Veneer Leaf Checklist link.

Lay on preparation

We recommend to slip-match fineline, rift quarter cut and straight grain veneers. Crown-cut veneers can be aesthetically pleasing book-matched or slip-matched depending on the application. The ultimate choice, be it book-matched or slip-matched lies with the client. In selected colours a pre-joined 1250mm wide leaf is available. These veneers have been joined using a superior Ruckle glued joint.

Guarantee

New Age Veneers Pty Ltd guarantees the intrinsic qualities of **Enviroven Veneers**. Discoloration due to exposure to sunlight and ultraviolet rays cannot be considered a material defect. In the event of any dispute, the guarantee and liability of **New Age Veneers Pty Ltd** is limited to the replacement of any material shown to be defective.

New Age Veneers Pty Ltd reserves the right to discontinue any designs or products without notice at any time.